

USP/Ph.Eur.

## **Test Certificate**

Part:

## **Basket without Lock**

Number:

02830

Serial Number:

N11000001 - N11000502

For SOTAX AT Dissolution Testing Systems



		Tolerances	
Dimensions: Basket rim O.D. Ø	25.0 mm	± 3.0	mm
Height	37.0 mm	± 3.0	mm
Wire Ø	0.25 mm	0.22 – 0.31 mm	
Wire openings	0.4 mm	0.36 - 0.44 mm	
Screen opening height	27.0 mm	± 1.0	mm
Screen O.D. Ø	22.2 mm	± 1.0	mm
Clear opening Ø	20.2 mm	± 1.0	mm
	Height Wire Ø Wire openings Screen opening height Screen O.D. Ø	Height37.0 mmWire Ø0.25 mmWire openings0.4 mmScreen opening height27.0 mmScreen O.D. Ø22.2 mm	Basket rim O.D. Ø $25.0 \text{ mm}$ $\pm 3.0$ Height $37.0 \text{ mm}$ $\pm 3.0$ Wire Ø $0.25 \text{ mm}$ $0.22 - 0.$ Wire openings $0.4 \text{ mm}$ $0.36 - 0.4$ Screen opening height $27.0 \text{ mm}$ $\pm 1.0$ Screen O.D. Ø $22.2 \text{ mm}$ $\pm 1.0$

Material: Stainless Steel

The accuracy of the above mentioned part dimensions have been examined. All relevant measurements are within tolerance and the factory acceptance test has passed. The dimensions are in conformance with USP and Ph. Eur. Pharmacopeia requirements (at time of delivery).

SOTAX Quality Management Bruno Balli 2018-05-31

Signature