


Automated Disintegration Basket Part

(for 6 Tubes, 10 mesh)

14678-01 Part Number

6302 - 6356 Serial Number



Effective dimension

	USP / Ph.Eur	Tolerances
Bottom plate Ø	90.0 mm	± 2.0 mm
Bottom thickness	6.75 mm	± 1.75 mm
6 Holes Ø	24 mm	± 2.00 mm
Mesh apertures	1.8 to 2.2 mm	
Mesh wire	0.57 to 0.66 mm	
PMMA, POM, PVC, PA, Stainless Steel		
	Bottom thickness 6 Holes Ø Mesh apertures Mesh wire	Bottom plate Ø 90.0 mm Bottom thickness 6.75 mm 6 Holes Ø 24 mm Mesh apertures 1.8 to 2.2 mm Mesh wire 0.57 to 0.66 mm

USP / Ph.Eur conformity (acc. USP701 / Ph Eur 2.9.1):

The design of the basket-rack assembly may be varied somewhat, provided the specifications for the glass tubes and the screen mesh size are maintained.

(separate Certificates for Glass tube #12514)

The accuracy of the above mentioned part dimensions have been examined. All relevant measurements are within tolerance and the factory acceptance test has passed.

Aesch, 2021-11-11

Bruno Balli

SOTAX Quality Management SOTAX AG | Nordring 1 | 4147 Aesch | Switzerland

1/1